


ABB Robotics Product Range

ABB Robotics is a pioneer in robotics and digital services, providing innovative solutions for a diverse range of industries, from automotive to electronics to logistics. As one of the world's leading robotics suppliers, we have shipped more than 500,000 robot solutions. We help our customers of all sizes to increase productivity, flexibility and simplicity and to improve output quality. We support their transition towards the connected and collaborative factory of the future. ABB Robotics & Discrete Automation employs more than 11,000 people at over 100 locations in more than 53 countries.

Technology and application leadership

"Robotics +" customer value stack





Years since we invented the first commercial microprocessor-controlled industrial robot. 500,000+

ABB robots shipped worldwide.

1,500 people


People working in our global service network.


Product range

Wide variety of robots to fit all needs

Robot types







Value propositions and applications



Enable simplicity



Enhance flexibility





Increase productivity



Optimize performance



Ensure consistent quality production



Help employees with their tasks

Applications according to IFR:

- · Handling operations, machine tending
 - Metal casting
 - Plastic moulding
 - Stamping, forging, bending
 - Inspection, testing
 - Packaging, picking, placing
 - Palletizing
 - Material handling
- Welding:
 - Arc welding
 - Spot welding
 - Laser welding
 - Soldering
- · Assembling, disassembling
- Cleanroom
- · Dispensing, painting
- · Processing:
 - Laser cutting
 - Water jet cutting
 - Mechanical cutting, grinding, deburring, milling, polishing





800 kg

| ticulate | ed robots | Payload (kg) | Reach (m) | Pos. rep. (mm) | Mounting | Protection and special design | Axes | Controller | Remark |
|----------|-----------------------|---------------------------------------|---|---|--|---|------|------------|---------------------------|
| | IRB 1100 | 4 4 | 0.475 0.58 | 0.01 | Any angle | Std: IP40 Option: Clean Room ISO 4, IP67 | 6 | OmniCore™ | |
| 1 | IRB 1200 | 5 7 | 0.90 0.70 | 0.025 0.02 | Any angle | Std: IP40. Option: Foundry Plus 2, IP67, Clean Room ISO 3, Food Grade Lubrication | 6 | IRC5 | |
| 1 | IRB 1300 | 7 10 11 | 1.4 1.15 0.9 | 0.03 0.023 0.02 | Any angle | Std: IP40 Option: IP67, Foundry Plus 2, Cleanroom ISO 4 | 6 | OmniCore™ | |
| 2 | IRB 140 IRB 140T | 6 | 0.80 | 0.03 | Floor, wall, inverted, tilted | Std: IP67. Option: Foundry Plus 2, Clean Room ISO 6, SteamWash | 6 | IRC5 | |
| 7 | IRB 1410 | 5 | 1.44 | 0.025 | Floor | Std: IP54 | 6 | IRC5 | |
| | IRB 1520ID | 4 | 1.50 | 0.05 | Floor, inverted | Std: IP40 | 6 | IRC5 | |
| 7 | IRB 1600 | 6 10 | 1.20/1.45 1.20/ 1.45 | 0.02 0.02/0.05 | Floor, wall, inverted, tilted, shelf | Std: IP54 Option: Foundry Plus 2 with IP67 | 6 | IRC5 | |
| 1 | IRB 1660ID | 4 6 | 1.55 | 0.02 | Floor, wall, inverted, tilted | Std: IP40 | 6 | IRC5 | |
| 7 | IRB 2400 | 12 20 | 1.55 | 0.03 | Floor, inverted | Std: IP54 Option: Foundry Plus 2 with IP67 | 6 | IRC5 | |
| 1 | IRB 2600 | 12/12 20 | 1.65/1.85 1.65 | 0.04 | Floor, wall, inverted, titled, shelf | Std: IP67, IP54 (axis 4) Option: Foundry Plus 2 | 6 | IRC5 | |
| 1 | IRB 2600ID | 15 8 | 1.85 2.00 | 0.026 0.023 | Floor, wall, shelf, titled, inverted | Std: IP67 for base and lower arm. IP54 for upper arm | 6 | IRC5 | |
| ,, | IRB 4400 IRB 4400L | 60 10 | 1.96 2.55 | 0.05 0.05 | Floor | Std: IP54 Option: IP67, Foundry Plus 2 | 6 | IRC5 | |
| 1 | IRB 4600 | 20/40/ 45/60 | 2.5/2.55/ 2.05/2.05 | 0.05 - 0.06 | Floor, inverted, tilted, shelf | Std: IP67 Option: Foundry Plus 2, Foundry Prime 2 | 6 | IRC5 | |
| | IRB 6620 | 150 | 2.20 | 0.03 | Floor, tilted, inverted | Std: IP54 Option: Foundry Plus 2 with IP67 | 6 | IRC5 | |
| - | IRB 6650S | 90 125 200 | 3.90 3.50* 3.00* | 0.13 0.14 | Shelf | Std: IP67, Option: Foundry Plus 2. High pressure steam washable | 6 | IRC5 | *Available with LeanID |
| | IRB 6660 | 100 130 205 | 3.30 3.10 1.90 | 0.10 0.11 0.07 | Floor | Std: IP67 Option: Foundry Plus 2 | 6 | IRC5 | |
| | IRB 6700 | 150/155/175 200/205/235 245/300 | 3.20/2.85/3.05 2.60/2.80/2.65 3.00/2.70 | 0.06/0.08/0.05 0.05/0.05/0.05 0.05/0.06 | Floor | Std: IP67 Option: Foundry Plus 2 | 6 | IRC5 | Available with LeanID |
| | IRB 6700INV | 245 300 | 2.90 2.60 | 0.06 0.05 | Inverted | Std: IP67 Option: Foundry Plus 2 | 6 | IRC5 | Available with LeanID |
| 39 | IRB 7600 | 150/325/ 340/400/ 500 | 3.50/3.10*/ 2.80*/2.55*/ 2.55 | 0.19/0.10 0.27/0.19 0.08 | Floor | Std: IP67 Option: Foundry Plus 2 | 6 | IRC5 | *Available with LeanID |

| Articulat | ed robots | Payload (kg) | Reach (m) | Pos. rep. (mm) | Mounting | Protection and special design | Axes | Controller | Remark |
|------------|---|------------------------|-------------------------------------|-----------------------------------|--|--|-------------|----------------------|--|
| 1 | IRB 8700 | 550 800 | 4.20 3.50 | 0.08 0.05 | Floor | Std: IP67 Option: Foundry Plus 2 | 6 | IRC5 | Available with LeanID |
| Cobots | | , | | , | , | | | | |
| 4 | CRB 15000 GoFa™ | 5 | 0.95 | 0.05 | Any angle | Std: IP54 | 6 | OmniCore™ | Functional safety Category 3, PL o |
| | CRB 1100 SWIFTI™ | 4 4 | 0.475 0.58 | 0.01 | Any angle | Std: IP40 | 6 | OmniCore™ | Functional safety Category 3, PL o |
| | IRB 14000 YuMi® | 0.50 | 0.559 | 0.02 | Table | Std: IP30 and Clean Room ISO 5 | 14 | Embedded IRC5 | Functional safety Category B, PL b |
| 9 | IRB 14050 YuMi® | 0.50 | 0.559 | 0.02 | Any angle | Std: IP30 and Clean Room ISO 6 | 7 | OmniCore™ | Functional safety Category 3, PL d |
| Parallel r | obots | | | | | | | | |
| | IRB 390 FlexPacker™ | 10 15 | 1.3 1.3 | 0.08 0.01 | Inverted | Std: IP67, Food Grade Lubrication | 5 4 | IRC5 | |
| \$ | IRB 360 FlexPicker® | 1 3 6 8 | 1.13/1.60 1.13 1.60 1.13 | 0.09/0.03 0.06 0.03 0.05 | Inverted | Std: IP54/67/69K, Food Grade Lubrication Option: Clean Room, Wash-down, Stainless | 4 | IRC5 or OmniCore™ | |
| SCARA ro | | | | , | , | | | | , |
| | IRB 910SC | 3 (max 6) | 0.45 0.55 0.65 | 0.01 | Table | Std: IP20 | 4 | IRC5 | |
| | IRB 910INV | 1 (max 3) 3 (max 6) | 0.35 0.55 | 0.01 0.01 | Inverted | Std: IP30. Option: Clean Room ISO 1, IP54 | 4 | OmniCore™ | |
| Paint rob | ots | | | | | | | | |
| | IRB 52 | 7 | 1.20/1.45 | 0.15 | Floor, wall, inverted, tilted | Std: IP66, Ex | 6 | IRC5P | |
| 3 | IRB 5500-22 IRB 5500-23 IRB 5500-25 FlexPainter® | 13 | 2.97 | 0.15 | Floor, wall, inverted, tilted Elevated | Std: IP66, Ex | 6 7 7 | IRC5P | |
| 9 | IRB 5500-27 FlexPainter® | 13 | 2.97 | 0.15 | Wall, floor, inverted | Std: IP66, Ex | 7 | IRC5P | |
| -3 | IRB 5510 | 13 | 2.56 | 0.15 | Floor | Std: IP66, Ex | 6 | IRC5P | |
| 7. | IRB 5350 | 7 | 1.35 Rail travel length: 3-10 | 0.15 | Floor, rail | Std: IP66, Ex | 3/4 | IRC5P | |
| Palletizin | ng robots | | | | | | | | |
| | IRB 460 | 110 | 2.40 | 0.20 | Floor | Std: IP67 | 4 | IRC5 | |
| | IRB 660 | 180 250 | 3.15 | 0.05 | Floor | Std: IP67 | 4 | IRC5 | |
| | IRB 760 | 450 | 3.18 | 0.05 | Floor | Std: IP67 | 4 | IRC5 | |
| Compliant | with ISO 9283. | | | Pose repeatability | | | | | |



GoFa™ CRB 15000 go far with your new helping hand

SWIFTI™ CRB 1100 unleash the speedy cobot






FlexPacker™ IRB 390 ultra-fast high payload picking and packing



IRB 1300 class-leading powerful performance in a compact package

PixelPaint unmasks the future of customized automotive painting





RobotStudio® AR viewer offers Augmented Reality on a smartphone

Key innovations

Expertise and support you can rely on

ABB Robotics is a pioneer in robots, software and advanced digital services, and has supplied many breakthrough innovations since introducing the world's first micro-processor-controlled robot in 1974.

- 1974 IRB 6, the world's first micro-processor-controlled robot
- **1979** IRB 60 the world's first electrical robot for spot welding
- 1983 First joystick FlexPendant for robot control
- 1986 IRB 2000, first robot driven by AC motors
- 1994 Dynamic motion control with TrueMove and QuickMove
- 1995 The world's highest speed delta robot
- 1998 RobotStudio, first offline programming tool

- **2001** IRB 7600, first industrial robot to handle 500 kg
- 2004 MultiMove, coordinated multiple (up to four) robot control
- 2005 Remote Services, a decade before the term 'internet of things' was known
- 2010 IRB 460 The fastest palletizing robot in the world
- 2015 YuMi, the world's first truly collaborative robot; ABB Connected Services
- 2018 OmniCore; world's first connected paint atomizer
- 2021 GoFa and SWIFTI, the next generation of cobots







Strongly positioned to benefit from market dynamics

Broadest portfolio amongst our peers

As the only player with both a strong robotics and automatio portfolio in-house, we are in an ideal position to provide our customers with flexible automation solutions from individual machines to whole plants. We have a balanced portfolio of products, cells and solutions, systems and services. Integrated solutions like machine-centric robotics and digital services open new high growth applications.

Innovation strength

We are expanding our portfolio of products (e. g. track systems), solutions (e. g. machine-centric robotics), cells and systems (e. g. flexible manufacturing systems). We focus especially on our software and digital portfolio. We already monitor ~9000 installed robots remotely and are constantly adding new digital services on ABB Ability. We have established incubators to accelerate the developments in artificial intelligence, digital factory automation, collaborative robotics and healthcare.

A true global player

We are very well positioned to serve our customers globally. We have local sales, service and application engineers in all relevant markets, and we produce robots in Sweden, China and the USA. With six R&D centers in Europe, Asia and the USA, we can tap into talent pools across the globe and do research close to all key markets.

Applied domain expertise

Deep domain know-how is the base for the development of value creating solutions to serve our customers. Through the alignment of our organization with customer segments, we are best positioned to serve their specific needs.

